S-27 LDF Specialty Fiber Fusion Splicer



Designed for Large Diameter Fiber Splicing



- Compact size, light weight, easy to carry
- Support 4000 groups fusion records
- Typical splicing time less than 15 seconds
- Comply with CE/RoHS international standard
- Accurate alignment, world standard fusion loss
- USB port for software upgrading, records exporting
- Easy to maintain, easy to replace the electrodes
- ❖ Applicable to cladding diameter 125~250/250~440µm
- Applicable to different types fibers(SM/MM/DS/NZDS)
- Ruggedized body, water-resistant, anti-dust, anti-shock

MORE INFO



Precise structure design, ensure fiber alignment



Two models optional for large clad diameter fiber



Good workmanship stable performance



Robust design, anti-shock dustproof&waterproof



Low splicing loss reach world standard



Completed accessories convenient for work

S-27 LDF Specialty Fiber Fusion Splicer

SPECIFICATIONS

Model	S-27-250	S-27-400		
Alignment Method	Clad to clad			
Cladding Diameter	125~250μm	250~400μm		
Coating Diameter	250 ~ 800μm			
Splicing Program	40 modes			
Typical Splice Time	14 seconds			
Typical Heating Time	30 seconds			
Operation Mode	Manual/ Auto			
Heating Mode	Manual/Auto			
Fiber Magnification	120X(X or Y view), 60X(X and Y view)			
Viewing Display	Dual high sensitivity camera, 5" HD color LCD Monitor			
Loss Evaluation	Auto			
Tension Test	1.8~2.2N			
Interface	GUI menu interface, easy for operation			
Power Supply	Adaptor, input: AC100~240V(50/60Hz), output: DC11~13.5V, 10A			
Electrode Life	125μm: 3000 arcs; 250μm: 1000 arcs			
Terminal	USB 2.0 port, for software upgrading, records exporting			
Operating Condition	Altitude: 0~5000m; Humidity: 0~95%; Temperature: -10°C~+50°C; Max wind: 15m/s			
Dimension/Weight	155mm(L)×144mm(W)×155mm(H)/1.80kg			

PACKAGE

Items	Qty	Items	Qty	Items	Qty
S-27-250	1pc	Power Plug	1pc	Spare Electrodes	1pair
Fiber Holders(250)	1pair	Power Adapter	1pc	Cooling Tray	1pc
Fiber Stripper(250)	1pc	User Manual(USB driver)	1pc	Carry Case	1pc
Items	Qty	Items	Qty	Items	Qty
S-27-250	1pc	Power Plug	1pc	Spare Electrodes	1pair
Fiber Holders(400)	1pair	Power Adapter	1pc	Cooling Tray	1pc
Fiber Stripper(400)	1pc	User Manual(USB driver)	1pc	Carry Case	1pc