



## Specially Designed for Cladding Diameter 80-460 $\mu$ m fiber



- ❖ Small and light
- ❖ Pluggable battery, support separate charge
- ❖ Easy to move and carry
- ❖ Normal 700 cuts on a full charge
- ❖ Adapt to a variety of complex work environments
- ❖ High working efficiency

### SPECIFICATIONS

Number of Fibers	Single
Cladding Diameter	80 $\mu$ m~460 $\mu$ m
Coating Diameter	160 $\mu$ m~600 $\mu$ m
Cleaved Length	2~22mm
Cleaved Angle	Typical 0.5°
Cleaved Method	Applying tension and blade scoring
Blade and Lifetime	Diamond blade, 10 cutting positions*2000 times per position(125 $\mu$ m cladding fiber)
Power Supply	Adaptor , input: AC100-240V(50/60Hz) , output:DC11~13.5V 5A
Dimension/ Weight	197mm(L) $\times$ 110mm(W) $\times$ 135mm(H)/ 2.3kg(with battery)
Operating Condition	Humidity: 0~95% , Temperature:0~+40°C(no condensation )

### PACKAGE

Item	Qty	Item	Qty	Item	Qty
XFC-02Main Machine	1unit	Power Adapter	1pc	Certificate of Conformity	1pc
Tool(01/02)	1set	User Manual	1pc	—	—