

# X-0563 Optical Power Meter & VFL



## FEATURES

- ❖ Auto calibration, auto power-off
- ❖ Wavelength memory function
- ❖ High accuracy, high sensitivity, high linearity
- ❖ Stable VFL output
- ❖ USB charge port
- ❖ Lower power consumption design, long standby time
- ❖ Rubber shell improves the protection performance in field operations
- ❖ Compact size, friendly operation interface, broad power measurement range

## Specifications

Type	X-0563-A	X-0563-C
Optical Power Meter Module		
Detector Type	InGaAs	
Measurement Range	-70dBm~+6dBm	-50dBm~+26dBm
Power Measurement	±0.1 dB	
Display Resolution	±0.01 dB	
Accuracy	±0.2 dB	
Power Display Units	dBm,mW,μW	
Optical Connector	ST/SC/FC /2.5mm Universal	
Visual Fault Locator Module		
Output Power	1mW/10mW/20mW/30mW	
Connector	ST/SC/FC/2.5mm universal	
Laser Safety Rating	Class II	
Wavelength	650nm±20nm	

# X-0563 Optical Power Meter & VFL

Output Modes	Continuous(CW), 2Hz pulsed
Reverse Battery Protection	Yes
General Information	
Power Supply	2000mAh Li-con battery
Auto Off	10 mins
Working time	>200hrs ( only OPM work )
Working Temperature	-10~+45°C
Dimensions/Weight	160x75x10mm/250g
Package	X-0563 power meter; FC/SC connector; user manual; soft bag; power charger